

# **Repair Aftercare Instructions**

**Your vehicle's repair has been cured and is able to withstand whatever the Great British weather throws at it! However, there are some guidelines below to ensure your repair stays looking its best for as long as possible!**

- DO NOT WASH THE VEHICLE WITH A HIGH PRESSURE WASHER FOR AT LEAST 3 DAYS.
- DO NOT APPLY WAXES, SEALANTS OR CERAMIC COATINGS TO THE VEHICLE FOR AT LEAST ONE MONTH. THIS IS TO ALLOW THE FRESH PAINT TO BREATHE AND PREVENT SOLVENT POP ISSUES.
- DO NOT APPLY PAINT PROTECTION FILMS OR WRAPS TO THE VEHICLE FOR AT LEAST 3 MONTHS. THIS IS TO ALLOW THE FRESH PAINT TO BREATHE AND PREVENT SOLVENT POP ISSUES.
- DO NOT COVER THE VEHICLE WITH A VEHICLE COVER FOR AT LEAST 3 MONTHS. THIS IS TO ALLOW THE FRESH PAINT TO BREATHE AND PREVENT SOLVENT POP ISSUES.
- REMOVE ANY TREE SAP DEPOSITS OR BIRD DROPPINGS IMMEDIATELY USING A CLEAN MICROFIBRE CLOTH AND WARM, SOAPY WATER. SOAK THE MICROFIBRE IN THE SOLUTION AND PLACE OVER THE DEPOSITS AND ALLOW 10 MINUTES BEFORE WIPING AWAY. REPEAT AS NECESSARY.